

META

Motor-driven diaphragm metering pump

The pump for simple applications.

- Capacity range 65 – 1,000 l/h, 10 – 3 bar
- Robust construction with Cast iron housing



ProMinent[®]

Type	Pump capacity at maximum back pressure			Max stroke frequency	Connection	Suction lift	Shipping weight
	bar	l/hr.	ml/stroke				
MTMa				strokes/min	Thread - pipe	mWS	kg
Prominent Meta (MTMa) : 0.18 kW motor 1440 rpm at 50 Hz							
12065	10	65	15.0	72	G1-1/4" - DN20	5	16
12086	10	86	15.0	96	G1-1/4" - DN20	5	16
12130	10	130	15.0	144	G1-1/4" - DN20	3	16
Prominent Meta (MTMa) : 0.37 kW motor 1440 rpm at 50 Hz							
10173	10	173	30.0	96	G1-1/4" - DN20	3	19
10260	10	260	30.0	144	G1-1/4" - DN20	3	19
05530	5	530	61.3	144	G1-1/2" - DN25	2	22.5
09395	9	395	45.7	144	G1-1/4" - DN20	3	19
03960	3	960	83.3	192	G1-1/2" - DN25	2	22.5
*041000	4	1000	86.8	192	G1-1/2" - DN25	2	22.5
Prominent Meta (MTMa) : 0.75 kW motor 1440 rpm at 50 Hz							
08530	8	530	61.3	144	G1-1/2" - DN25	2	25
05790	5	790	89.7	144	G1-1/2" - DN25	2	25

*Special product, Available on request

Electrical: 3 Phase 220V/380V 50Hz Enclosure: IP 55

Reproducibility accuracy +/-2% (When used in accordance with operating instruction & no change in back pressure)

Note: the above accuracy is applicable when the pump runs at/above 30% of the full speed/stroke length

Package not include accessories

Wetted materials				
Liquid end	Dosing head	Suction/Discharge connector	Valve Ball	Seal
PP	PP	PP	Ceramic	EPDM

DEVELOPAN[®] Diaphragms with PTFE support in all versions



ProMinent Fluid Controls (Thailand) Co., Ltd.
 2991/7 Ladprao Rd., Klongchan, Bangkok, Bangkok 10240
 Tel. 02-376-0008 Fax. 02-376-0013